

You need fresh air, so does your home.



Greentek Peace of Mind

All Greentek products are backed by the best limited warranty in the industry, for your peace of mind.

You benefit from a lifetime warranty on the core, a 10-year warranty on our ventilation motors and a 5-year warranty on all other components. So you can breathe easy.





Heat Recovery Ventilator PH Series (PH 7.15 and PH 10.22)







DuoTrol balancing system

Silent and economical... By reducing motor speed to balance the unit, you avoid the noise that would be produced

by balancing dampers. In addition, with this technology the unit will consume less energy.



Balancing Pressure Taps

Quick and easy integrated balancing pressure taps located in the access door allows for accurate readings and maximizing your balanced

ventilation requirements.



6" (diam.) collar system

Quick and simple to install thanks to our revolutionary "Insert Slide and Fix" collar system. The "ISF" 6" (diam.)

collar system enables you to manipulate duct within your reach and then insert by sliding it in place, for a better and quicker installation.



Range of controls For optimal performance of your HRV/ERV system.

The entire range of controls is offered with features making your ventilation system simple,

easy to operate and backed by a 5-year limited warranty. Choose from: EHC1.5, EHC1.0, RD-1, RD-2, RD-3P, RD-4P and T-3 (Push-Button Timer)




High-Performance motors

All Imperial products are designed with high-performance and reliable motors for your comfort and peace of mind. Factory sealed and dynamically

balanced, our motors are maintenance-free for years to come.

Ventilation Performance PH 7.15								
External Static Pressure		Net Supply Air Flow			Air Flow oply	Gross Air Flow Exhaust		
Pa	in. wg	L/s	CFM	L/s	CFM	L/s	CFM	
25	0.1	91	193	91	194	103	217	
50	0.2	84	178	85	179	95	201	
75	0.3	77	163	77	163	86	183	
100	0.4	71	150	71	151	80	169	
125	0.5	63	133	63	134	71	152	
150	0.6	57	120	57	121	66	138	
175	0.7	51	109	51	109	57	121	
HVI								



Vent	tilation	Perfo	rman	ce PH	10.22	2								
	al Static ssure		Supply Flow	Gross A Sup			Air Flow aust			l -Supply	-О-Б	haust		
Pa	in. wg	L/s	CFM	L/s	CFM	L/s	CFM	_	300	I				
25	0.1	119	252	119	252	121	256	= n x 0.4719)	250					
50	0.2	111	235	112	237	113	239	4.0	200	+			$\overline{}$	
75	0.3	103	218	104	220	104	220	×	150					
100	0.4	95	201	96	203	95	201	= s/:	400					
125	0.5	86	182	87	184	86	182	cfm (L/s	100					
150	0.6	79	167	79	167	77	163	Ъ	50				_	
175	0.7	70	148	70	148	68	144		ا ٥	0.1 0	.2 0.	3 0.4	4 0.	.5 0
HVI												nal Sta (Pa =		

E	ner	gy	Pert	PH 7.15			
	Supply Temperature			et Flow	Power Consumed	Sensible Recovery Efficiency	Adjusted Sensible Recovery Efficiency
	°C	°F	L/s	CFM	Watts	SRE %	ASRE %
HEATING	0	32	31	65	72	66	73
Ę	0	32	39	83	80	63	69
Ē	0	32	50	107	94	60	66
_	-25	-13	35	74	72	56	59

Er	ner	gy	Perf	PH 1	0.22		
	Supply Temperature		Net Air Flow		Power Consumed	Sensible Recovery Efficiency	Adjusted Sensible Recovery Efficiency
	°C	°F	L/s	CFM	Watts	SRE %	ASRE %
HEATING	0	32	29	61	62	75	82
퉑	0	32	43	91	74	72	78
\mathbf{H}	0	32	60	127	92	67	72
_	-25	-13	33	70	59	58	61

SPECIFICATIONS	PH 7.15	PH 10.22					
Size	23%" x 21½" x 11%"	23%" x 21½" x 16½"					
Weight	50 lbs (22.68 Kg)	65 lbs (29.48 Kg)					
CFM	30 to 160	70 to 220					
Type of heat exchanger	cross-flow (Polypropylene)	cross-flow (Polypropylene)					
Exchange surface	104 ft ²	150 ft ²					
Voltage	120 VAC @ 60 Hz	120 VAC @ 60 Hz					
Amperage	1.5 A	1.5 A					
Defrost type	Evacuation	Evacuation					
Certification	HVI, _c CSA _{us} ,	HVI, _c CSA _{us} ,					
	211/2" 6"	21½"					
Also available in PE Series (Energy Recovery Ventilator). Ideal for warm and humid climates.							



Greentek

50 Kanalflakt Way, Bouctouche, NB Canada E4S 3M5

Toll free: 1 888 724-5211 Fax: 1 (866) 426-7430 Visit us at: www.greentek.ca

You can find Greentek Indoor Air Quality products at the following distributor:







