

Features

- 48Y Frame
- 5.5" Diameter
- Open Enclosure
- Mounting: Stud, Strap & Base (Resilient Rings)
- 60 Hz
- Sleeve Bearing
- Shaft: 4.0" x 1/2"
- Reversible
- Permanent Split Capacitor (P.S.C.)
- 40°C Ambient
- Insulation Class B
- Thermally Protected



45°C Ambient

24 Month Warranty



92-A8617
Torsion Flex Bracket
5.0" & 5.5" Dia.
9" & 10" Bolt Circles



92-A8550 - 5" Diameter
92-A8555 - 5.5" Diameter
9" & 10" Bolt Circles



5.5" Diameter for
1/2 HP and above
92-A8556 - 9" Bolt Circle
92-A8557 - 10" Bolt Circle
HEAVY DUTY

115 & 208/230 Volt, 3 Speed, 1075 RPM, Reversible Rotation

Part #	HP	Volts	Amps	Cap.	SPD/RPM	Rotation	Body	Bearing	Shaft
DD-3583	1/4	115	4.8	5/370	3/1075	Revers.	4.22"	Sleeve	1/2"x4.0"
DD-3584	1/4	208/230	2.0	5/370	3/1075	Revers.	4.22"	Sleeve	1/2"x4.0"
DD-3585	1/3	115	5.5	7.5/370	3/1075	Revers.	4.37"	Sleeve	1/2"x4.0"
DD-3586	1/3	208/230	2.8	5/370	3/1075	Revers.	4.48"	Sleeve	1/2"x4.0"
DD-3587	1/2	115	7.5	10/370	3/1075	Revers.	5.25"	Sleeve	1/2"x4.0"
DD-3588	1/2	208/230	3.6	10/370	3/1075	Revers.	5.23"	Sleeve	1/2"x4.0"
DD-3589	3/4	115	10.2	15/370	3/1075	Revers.	5.48"	Sleeve	1/2"x4.0"
DD-3590	3/4	208/230	5.4	10/370	3/1075	Revers.	5.48"	Sleeve	1/2"x4.0"

Capacitor Not Included

Cross Reference

Rotom	HP	Voltage	AO Smith	Diversitech	Emerson	Fasco	Embraco	GE	Marathon	UE	Rotom
DD-3583	1/4	115	DL1026	WG840583	1863	D721	E201	3583	X000	533	R43583
DD-3584	1/4	208/230	D1026	WG840584	1971	D725	E202	3584	X001	530	R43584
DD-3585	1/3	115	DL1036	WG840585	1864	D727	E203	3585	X002	532	R43585
DD-3586	1/3	208/230	D1036	WG840586	1972	D923	E204	3586	X003	529	R43586
DD-3587	1/2	115	DL1056	WG840587	1865	D701	E205	3587	X004	531	R43587
DD-3588	1/2	208/230	D1056	WG840588	1973	D703	E206	3588	X005	528	R43588
DD-3589	3/4	115	DL1076	WG840589	8904	D728	E207	3589	X009	678	R43589
DD-3590	3/4	208/230	D1076	WG840590	8905	D729	E208	3590	X010	679	R43590