

Open Construction - Single Shaft

Sleeve & Ball Bearing - Shaded Pole & P.S.C.



Fig.1
R130



Fig.2
R332



Fig.3
R336
R421
R355
R313



Fig.4
R358
R368
R1052
R90031
R90030
R90032
R90033



Fig. 5
R394
R356
R357



Fig.6
R90572
R90574



Fig.7
R90672
R90671




Fig.8
R422




Fig.9
R384

Motors

1550 RPM-115, 208, 230 volts

3.3" Motors continued from previous page

| Part # | Amps | Volts | H.P. | Rot. | Shaft | Body | Feature | Comment | Fig. |
|--------|------|----------------|------|--------|-------------|------|-------------------------------------|-------------------------------------|------|
| R318 | 1.50 | 115 | 1/25 | C.W. | 2.8"x5/16" | 2.80 | U Brk | Blanchard 79105 | 1 |
| R332 | 1.50 | 115 | 1/25 | C.W. | 1.5"x5/16" | 2.60 | 2 Pin plug | Bohn / Blanchard | 2 |
| R336 | 1.50 | 115 | 1/25 | C.C.W. | 1.2"x1/4" | 2.60 | Special leads | W.C.Woods | 3 |
| R384 | 1.50 | 115 | 1/25 | C.W. | 1.5"x5/16" | 2.80 | Conduit Box | DELHI 8840011, RB245, 8213915061 | 9 |
| R90031 | 1.60 | 115 | 1/25 | CW | 2.57"x5/16" | 2.75 | 4 Studs front & rear | 31, 40031 | 4 |
| R90030 | 1.60 | 115 | 1/25 | CCW | 2.57"x5/16" | 2.75 | 4 Studs front & rear | 30, 40030 | 4 |
| R394 | 1.60 | 115 | 1/20 | C.W. | 2.5"x5/16" | 2.75 | Cord & Plug | Larkin 2531194 | 5 |
| R368 | 1.72 | 115 | 1/20 | C.W. | 2.5"x5/16" | 2.80 | 4 Studs + 2 pin plug | Ref. Plus RMT 0012 | 4 |
| R356 | 1.75 | 115 | 1/20 | C.C.W. | 2.2"x5/16" | 2.60 | 4 studs front & rear | Gen. Replacement | 5 |
| R357 | 1.75 | 115 | 1/20 | C.W. | 2.3"x5/16" | 2.60 | 4 studs front & rear | Gen. Replacement | 5 |
| R421 | 1.75 | 115 | 1/15 | C.C.W. | 2.3"x5/16" | 3.54 | Internal Fan Cooled, Studs front | Coleman | 3 |
| R90572 | 1.80 | 115 | 1/15 | CCW | 3.03"x5/16" | 3.00 | 2 Pin Plug | 572A, D1124, 45008S | 6 |
| R90133 | 1.80 | 115 | 1/20 | CW | 2.24"x5/16" | 2.75 | 4 studs front & rear | D133, 40133 | 4 |
| R90132 | 1.80 | 115 | 1/20 | CCW | 2.24"x5/16" | 2.75 | 4 studs front & rear | D132, 40132, 3M547 | 4 |
| R90574 | 1.90 | 115 | 1/20 | CW | 2.48"x5/16" | 2.75 | 2 Pin plug | 574, D1101, 41194 | 6 |
| R358 | 2.00 | 115 | 1/20 | C.C.W. | 3.2"x5/16" | 3.30 | 2 Pin plug | Blanchard E1058 | 4 |
| R1052 | 2.00 | 115 | 1/20 | C.C.W. | 3.2"x5/16" | 3.00 | 2 Pin plug | Blanchard E1052 | 4 |
| R90672 | 2.10 | 115 208/230 | 1/15 | CCW | 2.24"x5/16" | 5.00 | Mechanical Duty | 672, 81672 | 7 |
| R90671 | 2.10 | 115 208/230 | 1/15 | CW | 2.24"x5/16" | 5.00 | Mechanical Duty | 671, 81671 | 7 |
| R355 | 2.20 | 115 | 1/15 | C.W. | 1.9"x5/16" | 3.11 | Hex Hubs | Nutone | 3 |
| R313 | 2.30 | 115 | 1/15 | C.C.W. | 3.0"x5/16" | 3.60 | 2 Pin plug | Bohn | 3 |
| R422 | 2.90 | 115 | 1/6 | C.W. | 2.1"x3/8" | 4.90 | 3 lugs, 3/1690 RPM | Venmar HRV 02209 | 8 |

Rotation determined opposite shaft end
Double shaft determined at lead end

Shaft length measured from hub
face to shaft end